

MTP FIBER TAP

OPTIMIZED FOR HIGH-DENSITY 40/100/400G NETWORKS

Profitap MTP fiber optic TAPs provide complete traffic visibility of 40GBASE-SR4, 100GBASE-SR4, and 400GBASE-SR8 networks with zero downtime, zero packet loss, and no point of failure. For optimal connectivity, our TAPs exclusively use US Conec MTP® connectors.

FEATURES


- Non-intrusive in-line monitoring
- Permanent network link guaranteed
- Monitoring of all OSI layers
- No packet loss, no point of failure
- Passive, unpowered
- High density

FIBER TYPE	Multi-Mode 50/125 µm, OM4, 850/1300 nm
SPLIT RATIO	50/50, can vary 3 to 4 %
MAXIMUM INSERTION LOSS	4.2 dB*
ENCLOSURE	Black & natural anodized aluminium
OPERATING TEMPERATURE	0°C to 50°C
STORAGE TEMPERATURE	-10°C to 80°C
HUMIDITY	10% to 90%, non-condensing


*Doesn't include external connector loss.



F8MY-SR4 TAP DIAGRAM



F8MY-SR8 TAP DIAGRAM



TECHNICAL SPECIFICATIONS

ORDER REFERENCE	F8MY-SR4	F8MY-SR8
CONNECTORS	24 x MTP 12p	24 x MTP 16p
LINKS	8	8
TYPE	40GBASE-SR4 / 100GBASE-SR4	400GBASE-SR8
DIMENSIONS (WxDxH)	430 x 180 x 15 mm 16.93 x 7.09 x 0.59 in	430 x 180 x 15 mm 16.93 x 7.09 x 0.59 in
FRONT PANEL DIMENSIONS (WxH)	484 x 15 mm 19.06 x 0.59 in	484 x 15 mm 19.06 x 0.59 in
WEIGHT	2310 g / 5.09 lb	2310 g / 5.09 lb