

X3-SERIES

ADVANCED TRAFFIC INTELLIGENCE FOR SECURITY AND PERFORMANCE ANALYSIS

Modern network monitoring and analytics do not only rely on packets. Security and NPM solutions need a complete visibility of the flow context. The pre-treatment layer must understand this context to offer the best-in-class level of traffic optimization.

The new generation of X3-Series Network Packet Brokers enables full visibility over packets and flows, as well as complex advanced processing for extended visibility. The X3-Series are the most versatile Network Packet Brokers, with both simple and very advanced features.

SSL/TLS Decryption

The X3-Series supports in-line and passive SSL/TLS traffic decryption. The TLS decryption feature reduces blindspots that exist with encrypted traffic. The X3-Series supports passive decryption of TLS 1.2 and below. TLS 1.3 in-line decryption is done via a proxy. Decrypted traffic can be sent to an out-of-band security or analysis appliance.

Data Masking

Decrypted traffic can expose confidential data to network engineers and analysts, resulting in security or privacy implications. The X3-Series can obfuscate sensitive data to comply with regulations and prevent data leakages. Data masking enables complete visibility into decrypted data without the risk of exposing sensitive data.

Deduplication

With TAPs and mirror ports at multiple points inside the network, the same network data may be captured multiple times, causing duplicate packets inside the monitoring system. Sending unnecessary duplicate packets to analysis and security tools significantly impacts their performance. The X3-Series can dynamically discard duplicated packets before they are sent out. Thanks to the large time window for packet comparison and extensive configurability of the deduplication feature, the X3-Series can mitigate multiple sources of duplicate packets, like network design flaws or switch SPAN ports.



FEATURE HIGHLIGHTS

- SSL/TLS decryption
- Data masking
- Packet deduplication
- TCP packet reordering and fragments re-assembling
- Full tunneling capability
- Packet Slicing
- IMSI Filtering / Correlation
- Timestamping
- Export NetFlow V5/V9
- L2-L7 Filtering, DPI
- Load Balancing
- Any-to-any Replication and Aggregation
- Microburst Protection

ORDER REFERENCES

ORDER REFERENCE	TYPE	PORTS	POWER SUPPLY
X3-880G-AC	Advanced Network Packet Broker	48 x 1G/10G, 4 x 40G/100G	100–240 VAC
X3-880G-DC	Advanced Network Packet Broker	48 x 1G/10G, 4 x 40G/100G	30–72 VDC
X3-440G-AC	Advanced Network Packet Broker	24 x 1G/10G, 2 x 40G/100G	100–240 VAC
X3-440G-DC	Advanced Network Packet Broker	24 x 1G/10G, 2 x 40G/100G	30–72 VDC
X3-880G-ID-AC	SSL/TLS In-Line Decryption	48 x 1G/10G, 4 x 40G/100G	100–240 VAC
X3-880G-ID-DC	SSL/TLS In-Line Decryption	48 x 1G/10G, 4 x 40G/100G	30–72 VDC
X3-440G-ID-AC	SSL/TLS In-Line Decryption	24 x 1G/10G, 2 x 40G/100G	100–240 VAC
X3-440G-ID-DC	SSL/TLS In-Line Decryption	24 x 1G/10G, 2 x 40G/100G	30–72 VDC

TECHNICAL SPECIFICATIONS

Management Interfaces	1 x RS232 (RJ45), 1 x Gigabit Ethernet (RJ45)	
Management Method	Local CLI, SSH, SNMPv2/v3, HTTP/HTTPS	
Dimensions (WxDxH)	446 x 558 x 44 mm — 17.56 x 21.97 x 1.73 in	
Weight	13.2 kg — 29.1 lb	
Power Consumption	Max. 440 W	
MTBF	161,485 hours	
Power Supply	100–240 VAC or 36–72 VDC	
Power Redundancy	Power module 1+1, hot swappable	
Fan	Fan module 4+1, hot swappable	
Operating Temperature	0–40°C — 32–104°F	
Relative Humidity	10–90% non-condensing	
FEATURE		
Supported Protocols	Ethernet, IP, ICMP, TCP/UDP/SCTP, BGP/OSPF/ISIS	
Supported Encapsulations	VLAN, VXLAN, MPLS, IP, GTP, GRE, L2TP/PPTP, IPSec (AH, ESP)	
Aggregation / Replication	Any-to-any	
Load Balancing	Hash based, weighted	
MATCH FILTER		
Wildcard N Tuple Rules	IPv4/IPv6, port, MAC, EtherType, MPLS Label, VLAN, VNI, TCP Flag, DSCP, Size, Fragment	
Deep Packet Inspection	Regex	
SSL / TLS DECRYPTION		
	Passive	In-line
Supported SSL / TLS Versions	SSL 3.0, TLS 1.0 – TLS 1.2	TLS 1.0 – TLS 1.3
Asymmetric Keys	RSA, ECDH	RSA, ECDH, ECDHE
Symmetric Keys	AES, RC4, 3DES	AES, 3DES
Hashing Algorithms	SHA, MD5	SHA, AEAD
Maximum Concurrent Sessions	300,000	300,000
Maximum TPS	30,000	10,000
Throughput	Up to 30 Gbps	Up to 10 Gbps
PACKET DEDUPLICATION		
Max. Window	1 second	
Max. Throughput	200 Gbps	
Signature Customization	MAC, TCP flags, TTL, L2, DSCP, Port	